(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 12 May 2005 (12.05.2005)

PCT

(10) International Publication Number WO 2005/041701 A1

(51) International Patent Classification7:

A24D 3/02

(21) International Application Number:

PCT/IB2004/003531

(22) International Filing Date: 27 October 2004 (27.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: BO2003Λ000641 31 October 2003 (31.10.2003)

(71) Applicant (for all designated States except US): G.D S.P.A. [TT/IT]; Via Battindarno, 91, I-40133 Bologna (IT).

(72) Inventors; and


(75) Inventors/Applicants (for US only): RIZZOLI, Salvatore [IT/IT]; Via Galeazza, 21, I-40132 Bologna (IT). BERTINELLI, Gianluca [IT/IT]; Via Calanchi, 6,

I-40011 Anzola Dell'Emilia (IT). GOBBI, Alessandro [IT/IT]; Via Fratelli Cervi, 43, I-40011 Anzola Dell'Emilia (IT). ZANETTI, Umberto [IT/IT]; Via Castellaro, 47, I-41100 Modena (IT).

- (74) Agents: BIANCIARDI, Ezio et al.; Bugnion S.p.A., Via Goito, 18, I-40126 Bologna (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A DEVICE FOR FEEDING FILTER RODS IN A FILTER TIP ATTACHMENT MACHINE



(57) Abstract: In a filter tip attachment machine, filter rods (2) are taken up from a hopper by a roller (5) furnished with longitudinal flutes (7), each accommodating one rod (2) and operating in conjunction with one or more rotating disc cutters (11) by which the rods (2) are divided into two or more plugs (10); the flutes (7) are sectional, incorporated into a set of axially slidable modules (17, 20, 23) ensheathing the take-up roller (5) and adjustable for position along the rolling surface according to the number of plugs (10) that will be cut from the rod (2), or to the length of the single plug (10), or both.

WO 2005/041701 A1